

Product data sheet

ProMix Plus for jointing and finish



Product description: ProMix Plus is a fine, ready-to-use and manual/machine processable filler acc. to DIN EN 13963 / Type 3A for indoor use.

Area of application: For the filling of joints of Rigips plasterboard constructions with Rigips paper tape and for the joint and surface finish on plasterboard surfaces, concrete, rough plaster surfaces and other substrate.

Technical specifications

Important

- Material that has already stiffened must not be used any more or «extended» by adding water. Risk of joint cracks.

Parameters	Sign	Value	Unit	Certification
Material				
Type of material		ready-mix filler		
Type				
Type		3A		EN 520
Building material class				
Fire behaviour		A2-s1, d0		EN 13501-1

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.

Product data sheet

ProMix Plus for jointing and finish

Parameters	Sign	Value	Unit	Certification
Filler / Plaster properties				
Surface Quality		Q1 Q2 Q3 Q4		IGG Merkblatt 2
Film thickness from		0	mm	
Film thickness till		3	mm	
Consumption with Q1		400	g/m ²	
Consumption with Q2		30	g/m ²	
Consumption with Q3		0.5	kg/m ²	
Consumption with Q4		1.4	kg/mm/m ²	
Processing temperature from		5	°C	
Processing temperature till		30	°C	
Sustrate condition		Solid Frost-free Clean of contaminants Dust-free Dry Sufficient dimensional stability		DIN 18350 / DIN V 18550

Notes

Storage		Dry Shady Air access Frost-free Cool		
Shelf life		12	months	
To be used after opening in		3	months	
Package Size		According to Pricelist		
Waste key number		17 09 04		

The values listed in this product data sheet only reflect the performance characteristics of the products. In addition, gypsum plaster systems have structural and structural properties, which can be found in our system documentation (e. g. Planen und Bauen).

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.